## NSN 5910-00-189-8653

Glass Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-189-8653 **Body Style:** W/o mtg facilities, terminal (s) on one surface Reliability Indicator: Not established **Terminal Length:** 0.750 inches **Body Length:** 0.375 inches **Body Width:** 0.188 inches **Body Height:** 0.078 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.270 inches and 0.300 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 2.200 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 105.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -25.0 to 25.0 single section **Tolerance Range Per Section:** -0.25 to 0.25 picofarads single section Case Material: Glass **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0010 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

N/a

Shelf Life:

## NSN 5910-00-189-8653

Glass Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0