## NSN 5910-00-190-0122

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-190-0122 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** 1.500 inches **Body Diameter:** 0.090 inches **Body Length:** 0.160 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 1000.000 picofarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -15.0/+15.0 without voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-milc39014/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5910-00-190-0122

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0