NSN 5910-00-191-1018

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-191-1018

| Body | C4. | ۱., |
|------|-----|-----|
| DOUV | SIV | le: |

W/mtg tabs/flanges, terminal (s) on one surfacew/mtg tabs/flanges, terminal(s) on one surfacew/mtg tabs/flanges, t

Reliability Indicator:

Not establishednot established

Terminal Length:

0.438 inches 0.438 inches 0.438 inches

Body Length:

1.750 inches

Body Width:

1.250 inches

Body Height:

1.125 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

24.000 microfarads single section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 65.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-191-1018

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0