# NSN 5910-00-191-1278

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-191-1278

### **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

## Terminal Length:

1.500 inches 1.500 inches 1.500 inches

#### **Body Diameter:**

0.138 inches

#### **Body Length:**

0.390 inches

#### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

2.200 microfarads single section

# Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

#### Dc Leakage At Maximum Operating Temp:

5.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Tantalum

#### **Dissipation Factor At Reference Tempurature In Percent:**

6.0000

# Dc Leakage At Reference Temp:

1.000 microamperes

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5910-00-191-1278

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0