NSN 5910-00-191-5390

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-191-5390

Body Style: W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.562 inches **Body Length:** 1.187 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 4000.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 2.200 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 350.0 dc single section **Tolerance Range Per Section:** -10.00 to 50.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 41.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-62+2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-191-5390

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0