NSN 5910-00-195-8502

Body Style:

N/a

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-195-8502

| W/mtg bracket, axial terminals | | | | | | |
|--|--|--|--|--|--|--|
| Reliability Indicator: | | | | | | |
| Not established | | | | | | |
| Terminal Length: | | | | | | |
| 3.000 inches | | | | | | |
| Body Diameter: | | | | | | |
| 0.688 inches | | | | | | |
| Body Length: | | | | | | |
| 1.750 inches | | | | | | |
| Terminal Diameter: | | | | | | |
| 0.025 inches | | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | | |
| 0.156 inches | | | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | | | | | | |
| 0.219 inches | | | | | | |
| Schematic Diagram Designator: | | | | | | |
| Electrod (s) grounded to case, w/gnd terminal | | | | | | |
| Anode Type: | | | | | | |
| Plain foil | | | | | | |
| Electrical Polarization: | | | | | | |
| Polarized | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | |
| 2 unthreaded mounting holes | | | | | | |
| Capacitance Value Per Section: | | | | | | |
| 25.000 microfarads single section | | | | | | |
| Nonderated Operating Temp: | | | | | | |
| Between -40.0 degrees celsius and 85.0 degrees celsius | | | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | | | |
| 25.0 dc single section | | | | | | |
| Tolerance Range Per Section: | | | | | | |
| -10.00/+150.00 percent single section | | | | | | |
| Case Material: | | | | | | |
| Metal | | | | | | |
| Capacitive Electrode Material: | | | | | | |
| Aluminum | | | | | | |
| Case Insulation Material: | | | | | | |
| Paper | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 uninsulated wire lead | | | | | | |
| Shalf Life: | | | | | | |

NSN 5910-00-195-8502

Electrolytic Fixed Capacitor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0