

View Online at <https://aerobasegroup.com/nsn/5910-00-196-1289>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.625 inches

Body Length:

2.188 inches

Body Width:

2.000 inches

Body Height:

1.594 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

18.0

Highest Frequency At Which Rf Current Rating Applies In KiloHertz:

3000.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

10.0

Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:

100.0

Unthreaded Mounting Hole Diameter:

0.196 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Section Quantity:

2

Capacitance Value Per Section:

100.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc all sections

Tolerance Range Per Section:

-5.00 to 5.00 percent 2nd section

Case Material:

Metal

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0