

View Online at <https://aerobasegroup.com/nsn/5910-00-196-1289>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

0.625 inches

**Body Length:**

2.188 inches

**Body Width:**

2.000 inches

**Body Height:**

1.594 inches

**Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:**

18.0

**Highest Frequency At Which Rf Current Rating Applies In KiloHertz:**

3000.0

**Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:**

10.0

**Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:**

100.0

**Unthreaded Mounting Hole Diameter:**

0.196 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Section Quantity:**

2

**Capacitance Value Per Section:**

100.000 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

250.0 dc all sections

**Tolerance Range Per Section:**

-5.00 to 5.00 percent 2nd section

**Case Material:**

Metal

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0