NSN 5910-00-197-6747 Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-197-6747  |
|--|
| Thread Class:  |
| 2a   |
| Body Style:  |
| Piston   |
| Body Length:   |
| 1.688 inches   |
| Overall Diameter:  |
| 1.281 inches   |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| -800.0 fifth section   |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:   |
| -100.0 to 100.0 all sections                                   |
| Individual Section Quantity:                                   |
| 6  |
| Mounting Facility Screw Thread Series Designator:              |
| Unc  |
| Inclosure Type:  |
| Encapsulated   |
| Mounting Facility Type And Quantity:                           |
| 2 threaded hole  |
| Thread Size:   |
| 0.138 inches   |
| Capacitance Range In Picofarads:                               |
| +60.0 to 110.0 third section                                   |
| Nonderated Voltage Rating And Type:                            |
| 500.0 ac peak all sections                                     |
| Adjustment Device Drive Type And Quantity:                     |
| 1 slotted screw  |
| Terminal Type And Quantity:                                    |
| 6 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A096a0   |