Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-198-5306

# Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.625 inches

**Body Length:** 

0.500 inches

#### **Body Width:**

0.471 inches

**Body Height:** 

#### 0.234 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

### **Capacitance Value Per Section:**

22000.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

500.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

# **Dissipation Factor At Reference Tempurature In Percent:**

0.5000

## **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0