Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-212-5969

# **Body Style:**

W/o mtg facilities, terminal (s) on one end

# **Reliability Indicator:**

Not established

# **Body Diameter:**

3.000 inches

## **Body Length:**

5.625 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Anode Type:

Plain foil

# Impedance At Minimum Operating Tempurature In Ohms:

#### 1.5

**Electrical Polarization:** 

Polarized

## **Capacitance Value Per Section:**

6800.000 microfarads single section

# Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

## **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

20.0000

Dc Leakage At Reference Temp:

1237.000 microamperes

## **Terminal Surface Treatment:**

Solder

#### Test Data Document:

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 threaded hole

## Shelf Life:

N/a

# Unit Of Measure:

# NSN 5910-00-212-5969

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0