NSN 5910-00-214-9332

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-214-9332

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Body Diameter:

Between 0.745 inches and 0.764 inches

Body Length:

2.234 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Extended foil

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware and hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

500.0 megohms

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.312 inches

Nonderated Continuous Voltage Rating And Type Per Section:

240.0 ac-rms single section and 400.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.5000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-00-214-9332

Plastic Dielectric Fixed Capacitor - Page 2 of 2



fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0