

View Online at <https://aerobasegroup.com/nsn/5910-00-220-3414>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.290 inches

Body Width:

0.290 inches

Body Height:

0.090 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

39000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-1.5/+1.5 without voltage applied single section

Nonderated Operating Temp:

Between -25.0 degrees celsius and 15.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-milc11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milc11015/19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Demilitarization:

No

Fiig:

A010b0