

View Online at https://aerobasegroup.com/nsn/5910-00-220-3421

# **Body Style:**

W/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not established

# Body Diameter:

0.225 inches

#### Body Length:

0.430 inches

# **Terminal Height From Body:**

1.250 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

# Capacitance Value Per Section:

2.200 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

#### **Tolerance Range Per Section:**

-0.25/+0.25 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

50000.0 megohms

#### **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-220-3421

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

