## NSN 5910-00-221-1447

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-221-1447

**Body Style:** 

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

Between 0.557 inches and 0.577 inches

**Body Length:** 

1.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.144 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:** 

1 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

150.0 megohms

**Capacitance Value Per Section:** 

0.680 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-25/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-221-1447

Paper Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0