NSN 5910-00-221-8116

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-221-8116

Body Style: W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Body Diameter:** 1.437 inches **Body Length:** 3.500 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 9.2 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1600.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 25.0000 Dc Leakage At Reference Temp: 424.000 microamperes **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

2 threaded hole

Specification Data:

Terminal Type And Quantity:

81349-mil-c-62/12 government specification

N/a

NSN 5910-00-221-8116

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0