Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-222-7431

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.500 inches

**Body Length:** 

0.790 inches

**Body Width:** 

0.420 inches

**Body Height:** 

0.250 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.345 inches and 0.405 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## **Capacitance Value Per Section:**

1500.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

#### **Power Factor At Reference Tempurature In Percent:**

0.6000

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-222-7431

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

