NSN 5910-00-223-3247

Capacitor Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-223-3247

Overall Length:3.812 inchesOverall Height:1.842 inchesOverall Width:0.750 inchesInside Length:2.906 inchesUnthreaded Mounting Hole Diameter:0.187 inches single mounting facilityDistance Between Mounting Facility Centers:3.312 inches single mounting facility single center groupDistance From Mounting Surface To Retaining Surface:1.812 inchesAccommodated Item Securing Device Type:Friction fastenerMounting Facility Type And Quantity:2 unthreaded hole single mounting facilitySteelSurface Treatment:PassivateStyle Designator:Flat strap footed hole mounting
Overall Height:1.842 inchesOverall Width:0.750 inchesInside Length:2.906 inchesUnthreaded Mounting Hole Diameter:0.187 inches single mounting facilityDistance Between Mounting Facility Centers:3.312 inches single mounting facility single center groupDistance From Mounting Surface To Retaining Surface:1.812 inchesAccommodated Item Securing Device Type:Friction fastenerMounting Facility Type And Quantity:2 unthreaded hole single mounting facilitySteelSurface Treatment:PassivateStyle Designator:
1.842 inchesOverall Width:0.750 inchesInside Length:2.906 inchesUnthreaded Mounting Hole Diameter:0.187 inches single mounting facilityDistance Between Mounting Facility Centers:3.312 inches single mounting facility single center groupDistance From Mounting Surface To Retaining Surface:1.812 inchesAccommodated Item Securing Device Type:Friction fastenerMounting Facility Type And Quantity:2 unthreaded hole single mounting facilityMaterial:SteelSurface Treatment:PassivateStyle Designator:
Overall Width:0.750 inchesInside Length:2.906 inchesUnthreaded Mounting Hole Diameter:0.187 inches single mounting facilityDistance Between Mounting Facility Centers:3.312 inches single mounting facility single center groupDistance From Mounting Surface To Retaining Surface:1.812 inchesAccommodated Item Securing Device Type:Friction fastenerMounting Facility Type And Quantity:2 unthreaded hole single mounting facilitySteelSurface Treatment:PassivateStyle Designator:
0.750 inches Inside Length: 2.906 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate
Inside Length: 2.906 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
2.906 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
 Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
0.187 inches single mounting facility Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
 Distance Between Mounting Facility Centers: 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
 3.312 inches single mounting facility single center group Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
Distance From Mounting Surface To Retaining Surface: 1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
1.812 inches Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
Accommodated Item Securing Device Type: Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
Friction fastener Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
2 unthreaded hole single mounting facility Material: Steel Surface Treatment: Passivate Style Designator:
Material: Steel Surface Treatment: Passivate Style Designator:
Steel Surface Treatment: Passivate Style Designator:
Surface Treatment: Passivate Style Designator:
Passivate Style Designator:
Style Designator:
Flat strap footed hole mounting
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A062a0