## NSN 5910-00-224-4770

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-224-4770

**Body Style:** 

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

**Terminal Length:** 

1.250 inches

**Body Diameter:** 

Between 0.220 inches and 0.290 inches

**Body Length:** 

Between 0.470 inches and 0.540 inches

**Terminal Diameter:** 

Between 0.023 inches and 0.027 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

1000.0 megohms

**Capacitance Value Per Section:** 

56.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-220.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-60.0/+60.0 single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.150

**Quality Factor At Reference Temp:** 

1000.000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-224-4770

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0