## NSN 5910-00-225-2395

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-225-2395

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.000 inches

**Body Length:** 

Between 0.990 inches and 1.010 inches

**Body Width:** 

Between 0.740 inches and 0.760 inches

**Body Height:** 

Between 0.370 inches and 0.390 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.895 inches and 0.950 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

2500.0 megohm-microfarads

**Capacitance Value Per Section:** 

2.400 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-225-2395

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0