## NSN 5910-00-225-8114

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-225-8114

### **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not establishednot establishednot established

## **Terminal Length:**

1.500 inches 1.500 inches 1.500 inches

#### **Body Diameter:**

0.125 inches

#### **Body Length:**

0.250 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### **Electrical Polarization:**

Polarized

#### **Features Provided:**

Hermetically sealed case

## **Capacitance Value Per Section:**

33000.000 picofarads single section

#### Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

Capacitive Electrode Material:

Tantalum

#### Dc Leakage At Reference Temp:

0.600 microamperes

#### **Terminal Surface Treatment:**

Solder

#### **Case Insulation Material:**

Plastic

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5910-00-225-8114

Electrolytic Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

