NSN 5910-00-226-0486

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-226-0486 **Thread Class:** Any acceptable **Body Style:** Piston **Overall Length:** 0.578 inches **Bushing Diameter:** 0.190 inches **Shaft Diameter:** 0.190 inches single shaft **Bushing Length:** Any acceptable **Shaft Length:** 0.250 inches single shaft **Body Length:** 0.328 inches **Overall Diameter:** 0.250 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0 to 50.0 single section Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -0.0 to 50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

NSN 5910-00-226-0486

Glass Dielectric Variable Capacitor - Page 2 of 2



Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+0.5 to 4.5 single section
Nonderated Voltage Rating And Type:
750.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0