## NSN 5910-00-227-0304

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-227-0304

Body Style:  W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end Reliability Indicator:  Not establishednot establishednot established Terminal Length: 0.500 inches 0.500 inches 0.500 inches Body Diameter: 1.438 inches Body Length: 3.500 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Electrical Polarization: Polarized Capacitance Value Per Section: 500.000 microfarads single section Nonderated Operating Temp:
Reliability Indicator: Not establishednot establishednot established Terminal Length: 0.500 inches 0.500 inches 0.500 inches Body Diameter: 1.438 inches Body Length: 3.500 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Electrical Polarization: Polarized Capacitance Value Per Section: 500.000 microfarads single section
Not establishednot establishednot established  Terminal Length: 0.500 inches 0.500 inches 0.500 inches  Body Diameter: 1.438 inches  Body Length: 3.500 inches  Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Anode Type: Plain foil  Electrical Polarization: Polarized  Capacitance Value Per Section: 500.000 microfarads single section
Terminal Length: 0.500 inches 0.500 inches 0.500 inches Body Diameter: 1.438 inches Body Length: 3.500 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Electrical Polarization: Polarized Capacitance Value Per Section: 500.000 microfarads single section
Body Diameter:  1.438 inches  Body Length: 3.500 inches  Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Anode Type: Plain foil  Electrical Polarization: Polarized  Capacitance Value Per Section: 500.000 microfarads single section
Body Diameter:  1.438 inches  Body Length: 3.500 inches  Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Anode Type: Plain foil  Electrical Polarization: Polarized  Capacitance Value Per Section: 500.000 microfarads single section
1.438 inches  Body Length: 3.500 inches  Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Anode Type: Plain foil  Electrical Polarization: Polarized  Capacitance Value Per Section: 500.000 microfarads single section
Body Length: 3.500 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches Schematic Diagram Designator: No common or grounded electrode (s) Anode Type: Plain foil Electrical Polarization: Polarized Capacitance Value Per Section: 500.000 microfarads single section
3.500 inches  Center To Center Distance Between Terminals Parallel To Diameter: 0.875 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Anode Type: Plain foil  Electrical Polarization: Polarized  Capacitance Value Per Section: 500.000 microfarads single section
Center To Center Distance Between Terminals Parallel To Diameter:  0.875 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Anode Type:  Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
0.875 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Anode Type:  Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Schematic Diagram Designator:  No common or grounded electrode (s)  Anode Type:  Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
No common or grounded electrode (s)  Anode Type:  Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Anode Type:  Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Plain foil  Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Electrical Polarization:  Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Polarized  Capacitance Value Per Section:  500.000 microfarads single section
Capacitance Value Per Section: 500.000 microfarads single section
500.000 microfarads single section
Nonderated Operating Temp
nonderated operating remp.
Between -20.0 degrees celsius and 65.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+100.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Terminal Surface Treatment:
Solder
Case Insulation Material:
Paper
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
Shelf Life: N/a

No

Demilitarization:

## NSN 5910-00-227-0304

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0