

View Online at <https://aerobasegroup.com/nsn/5910-00-230-7549>

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.187 inches

Body Diameter:

0.156 inches

Body Length:

0.375 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded mounting studs

Capacitance Value Per Section:

8.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 95.0 degrees celsius

Thread Size:

0.099 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-500.0/+500.0 single section

Tolerance Range Per Section:

-0.80/+0.80 picofarads single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0