

View Online at https://aerobasegroup.com/nsn/5910-00-230-7858

Body Style:	
Piston	
Overall Length:	
0.859 inches	
Shaft Length:	
0.125 inches single shaft	
Body Length:	
0.734 inches	
Overall Diameter:	
0.312 inches	
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:	
-150.0/+150.0 single section	
Center To Center Distance Between Terminals Parallel To Length:	
0.688 inches	
Center To Center Distance Between Terminals Parallel To Diameter:	
0.234 inches	
Quality Factor At 25 Deg Celsius:	
750.0	
Inclosure Type:	
Encased	
Adjustment Device Torque:	
Between 1.000 inch-ounces and 10.000 inch-ounces	
Insulation Dc Resistance At 25 Deg Celsius:	
1000.0 gigohms	
Insulation Dc Resistance At Max Operating Temp:	
100.0 gigohms	
Mounting Facility Type And Quantity:	
4 terminal	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Shaft Type:	
Round, slotted single shaft	
Capacitance Range In Picofarads:	
+1.0/+16.0 single section	
Nonderated Voltage Rating And Type:	
1000.0 dc continuous single section	
Adjustment Device Drive Type And Quantity:	
1 shaft	
Capacitance Drift In Picofarads:	
0.50 single section	
Test Data Document:	
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	วท
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Glass Dielectric Variable Capacitor - Page 2 of 2



## Terminal Type And Quantity:

4 wire lead

## Specification Data:

81349-mil-c-14409/9 government specification

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A096a0