NSN 5910-00-230-8633

Body Style:

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-230-8633

Piston **Overall Length:** 1.094 inches **Shaft Length:** 0.125 inches single shaft **Body Length:** 0.969 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -150.0/+150.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.922 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.234 inches **Quality Factor At 25 Deg Celsius:** 550.0 **Inclosure Type: Encased Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 100.0 gigohms **Mounting Facility Type And Quantity:** 4 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Shaft Type:** Round, slotted single shaft Capacitance Range In Picofarads: +1.0/+36.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 shaft **Capacitance Drift In Picofarads:** 0.08 single section **Test Data Document:** 81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-00-230-8633

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0