NSN 5910-00-232-2525

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-232-2525

9
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.313 inches
Body Diameter:
0.938 inches
Body Length:
2.125 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
500.0
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
5.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
360.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
450.0 dc single section
Tolerance Range Per Section:
-15.00/+75.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Equivalent Series Resistance At Reference Tempurature In Ohms:
13.00
Dc Leakage At Reference Temp:
45.000 microamperes
Case Insulation Material:
Plastic

_ . ._

Terminal Type And Quantity:

1 solder stud and 1 tab, solder lug

NSN 5910-00-232-2525

Electrolytic Fixed Capacitor - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0