NSN 5910-00-232-3127

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-232-3127

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Terminal Length:

12.000 inches

Body Length:

5.500 inches

Body Width:

3.300 inches

Body Height:

3.188 inches

Center To Center Distance Between Terminals Parallel To Length:

5.000 inches

Terminal Diameter:

0.090 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.000 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

4 threaded mounting holes

Section Quantity:

7

Capacitance Value Per Section:

2.000 microfarads 4th section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.164 inches

Nonderated Continuous Voltage Rating And Type Per Section:

6000.0 dc 7th section

Tolerance Range Per Section:

-10.00 to 10.00 percent all sections

Case Material:

Plastic

Insulation Resistance At Reference Temp:

5000.0 megohm-microfarads

NSN 5910-00-232-3127

Fiig: A010b0

Mica Dielectric Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature In Percent:	
0.500	
Quality Factor At Reference Temp:	
0.005	
Terminal Type And Quantity:	
11 uninsulated wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	