

View Online at <https://aerobasegroup.com/nsn/5910-00-233-4323>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 1.859 inches and 1.891 inches

Body Width:

Between 1.328 inches and 1.360 inches

Body Height:

Between 0.703 inches and 0.735 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.609 inches and 0.641 inches

Unthreaded Mounting Hole Diameter:

Between 0.149 inches and 0.159 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.828 inches and 1.860 inches

Internal Electrical Connection Type:

Extended foil

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Section Quantity:

3

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

0.500 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 ac-rms all sections and 250.0 dc all sections

Tolerance Range Per Section:

-3.00 to 10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

1.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0