## NSN 5910-00-235-2203

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-235-2203

Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.375 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
5.000 microfarads single section
ologo microrarado olingio occión
Nonderated Operating Temp:
-
Nonderated Operating Temp:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section  Case Material:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section  Case Material:  Metal
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section: -5.00 to 5.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section: -5.00 to 5.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Case Insulation Material:
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Case Insulation Material:  Plastic
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  400.0 dc single section  Tolerance Range Per Section:  -5.00 to 5.00 percent single section  Case Material:  Metal  Terminal Surface Treatment:  Solder  Case Insulation Material:  Plastic  Terminal Type And Quantity:

--

**Unit Of Measure:** 

## NSN 5910-00-235-2203

Paper Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0