Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-235-3104

# **Body Style:**

W/o mtg facilities, terminal (s) on one end

# **Reliability Indicator:**

Not established

# **Body Diameter:**

1.250 inches

## **Body Length:**

2.999 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

# Anode Type:

Plain foil

## Impedance At Minimum Operating Tempurature In Ohms:

1465.0

## **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

15.000 microfarads single section

# Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

450.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Aluminum

#### **Dissipation Factor At Reference Tempurature In Percent:**

17.0000

Dc Leakage At Reference Temp:

123.000 microamperes

#### **Terminal Surface Treatment:**

Nickel

#### **Case Insulation Material:**

Plastic

## **Test Data Document:**

81349-mil-c-62/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

4 standard tube base

Shelf Life:

N/a

# NSN 5910-00-235-3104

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0