NSN 5910-00-235-3107

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-235-3107

Body Style: W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Body Diameter:** 1.500 inches **Body Length:** 2.999 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 18.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 820.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 15.0000 Dc Leakage At Reference Temp: 304.000 microamperes **Terminal Surface Treatment:** Nickel **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-62/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

N/a

Shelf Life:

4 standard tube base

NSN 5910-00-235-3107

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0