Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-235-4441

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.630 inches

#### **Body Diameter:**

0.328 inches

#### **Body Length:**

0.900 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Features Provided:

Hermetically sealed case

#### Insulation Resistance At Maximum Operating Temp:

40000.0 megohms

## **Capacitance Value Per Section:**

6800.000 picofarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 65.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

#### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1000

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

# **Test Data Document:**

18876-10189408 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

# NSN 5910-00-235-4441

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0