

View Online at <https://aerobasegroup.com/nsn/5910-00-236-4498>

**Body Style:**

W/thd mtg hole/stud, terminal (s) on one end

**Reliability Indicator:**

Not established

**Width Across Flats:**

0.250 inches

**Terminal Length:**

0.405 inches

**Body Diameter:**

0.250 inches

**Body Length:**

0.520 inches

**Terminal Diameter:**

Between 0.062 inches and 0.072 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded mounting studs

**Capacitance Value Per Section:**

5000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-56.0/+22.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -56.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.099 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Thread Tolerance Class:**

2a external

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

100000000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

3.000

**Terminal Surface Treatment:**

Solder

**Precious Material And Location:**

Metal surfaces silver

**Terminal Type And Quantity:**

1 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0