Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-237-2571

### **Body Style:**

W/o mtg facilities, axial terminals

# Mil-std-1276 Wire Lead Type Designator:

N-2

### **Reliability Indicator:**

Not established

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.322 inches

#### **Body Length:**

0.813 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

### **Capacitance Value Per Section:**

0.680 microfarads single section

### Nonderated Operating Temp:

Between -62.0 degrees celsius and 100.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.2000

# **Terminal Surface Treatment:**

Gold

# Case Insulation Material:

Plastic

# Precious Material And Location:

Terminal surface gold

# Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0