## NSN 5910-00-239-0048

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-239-0048

Body Style:
W/thd bushing mtg, terminals on opposite ends
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Diameter:
0.400 inches
Body Length:
0.875 inches
Continuous Current Rating In Amps:
5.0
Schematic Diagram Designator:
Feedthrough
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
100.000 nanofarads single section
Nonderated Operating Temp:
Between 0.0 degrees celsius and 65.0 degrees celsius
Thread Size:
0.312 inches
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
6000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Type And Quantity:
2 tab, solder lug
Reference Number Differentiating Characteristics:
Navord od41152
Shelf Life:

N/a

## NSN 5910-00-239-0048

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0