

View Online at https://aerobasegroup.com/nsn/5910-00-239-0048

### **Body Style:**

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.312 inches

#### **Body Diameter:**

0.400 inches

#### **Body Length:**

0.875 inches

#### **Continuous Current Rating In Amps:**

5.0

#### Schematic Diagram Designator:

#### Feedthrough

#### Mounting Facility Screw Thread Series Designator:

# Unf

Mounting Facility Type And Quantity:

1 threaded bushing

#### **Features Provided:**

Hermetically sealed case

#### **Capacitance Value Per Section:**

100.000 nanofarads single section

#### Nonderated Operating Temp:

Between 0.0 degrees celsius and 65.0 degrees celsius

#### **Thread Size:**

0.312 inches

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

6000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Type And Quantity:**

2 tab, solder lug

# **Reference Number Differentiating Characteristics:**

Navord od41152

## Shelf Life:

N/a



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0