## NSN 5910-00-239-2046

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-239-2046

Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Body Length:
5.250 inches
Body Width:
2.125 inches
Body Height:
4.562 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.375 inches
Schematic Diagram Designator:
Quad, one common terminal for each pair
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
4 threaded mounting studs
Section Quantity:
4
Features Provided:
Features Provided: Hermetically sealed case
Hermetically sealed case
Hermetically sealed case  Capacitance Value Per Section:
Hermetically sealed case  Capacitance Value Per Section:  8.000 microfarads 4th section
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp:
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:
Hermetically sealed case  Capacitance Value Per Section:  8.000 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc all sections
Hermetically sealed case  Capacitance Value Per Section:  8.000 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections  Tolerance Range Per Section:
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc all sections  Tolerance Range Per Section: -10.00 to 10.00 percent 2nd section
Hermetically sealed case  Capacitance Value Per Section:  8.000 microfarads 4th section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size:  0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section:  600.0 dc all sections  Tolerance Range Per Section:  -10.00 to 10.00 percent 2nd section  Case Material:
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc all sections  Tolerance Range Per Section: -10.00 to 10.00 percent 2nd section  Case Material:  Metal
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc all sections  Tolerance Range Per Section: -10.00 to 10.00 percent 2nd section  Case Material:  Metal  Terminal Type And Quantity:
Hermetically sealed case  Capacitance Value Per Section: 8.000 microfarads 4th section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Thread Size: 0.164 inches  Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc all sections  Tolerance Range Per Section: -10.00 to 10.00 percent 2nd section  Case Material:  Metal  Terminal Type And Quantity: 6 tab, solder lug

--

## NSN 5910-00-239-2046

Paper Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0