

View Online at <https://aerobasegroup.com/nsn/5910-00-239-8214>

Body Style:

W/mtg hol (s)/slot(s), terminal(s) on one surface

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 0.560 inches and 0.600 inches

Body Width:

Between 0.145 inches and 0.165 inches

Body Height:

Between 0.055 inches and 0.075 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.444 inches and 0.456 inches

Terminal Diameter:

Between 0.050 inches and 0.060 inches

Schematic Diagram Designator:

One terminal common to each section

Section Quantity:

4

Capacitance Value Per Section:

0.010 microfarads all sections

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0 to 15.0 without voltage applied all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc all sections

Tolerance Range Per Section:

-0.00/+100.00 percent all sections

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.000

Terminal Surface Treatment:

Gold

Special Features:

width: 0.145 inch min. And 0.165 inch max., tolerance range per section: -0.00 to 100.00 percent all sections

Terminal Type And Quantity:

4 unthreaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0