

View Online at <https://aerobasegroup.com/nsn/5910-00-239-8214>

**Body Style:**

W/mtg hol (s)/slot(s), terminal(s) on one surface

**Reliability Indicator:**

Not established

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Body Length:**

Between 0.560 inches and 0.600 inches

**Body Width:**

Between 0.145 inches and 0.165 inches

**Body Height:**

Between 0.055 inches and 0.075 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.444 inches and 0.456 inches

**Terminal Diameter:**

Between 0.050 inches and 0.060 inches

**Schematic Diagram Designator:**

One terminal common to each section

**Section Quantity:**

4

**Capacitance Value Per Section:**

0.010 microfarads all sections

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-15.0 to 15.0 without voltage applied all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc all sections

**Tolerance Range Per Section:**

-0.00/+100.00 percent all sections

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.000

**Terminal Surface Treatment:**

Gold

**Special Features:**

width: 0.145 inch min. And 0.165 inch max., tolerance range per section: -0.00 to 100.00 percent all sections

**Terminal Type And Quantity:**

4 unthreaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0