## NSN 5910-00-240-8178

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-240-8178

**Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.687 inches **Body Length:** 1.687 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 1800.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 8.200 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 86.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Test Data Document:** 

81349-mil-c-62/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## NSN 5910-00-240-8178

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0