Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-240-9878

# **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.687 inches

**Body Length:** 

0.700 inches

#### **Body Width:**

0.370 inches

**Body Height:** 

#### 0.270 inches

## Center To Center Distance Between Terminals Parallel To Length:

Between 0.345 inches and 0.405 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

25.0 megohm-microfarads

## **Capacitance Value Per Section:**

56000.000 picofarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

25000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-240-9878

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

