NSN 5910-00-241-2877

Plastic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-241-2877 |
|---|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.000 inches |
| Body Length: |
| 0.781 inches |
| Body Width: |
| 0.250 inches |
| Body Height: |
| 0.343 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Internal Electrical Connection Type: |
| Extended foil |
| Insulation Resistance At Maximum Operating Temp: |
| 5000.0 megohm-microfarads |
| Capacitance Value Per Section: |
| 0.050 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 50000.0 megohm-microfarads |
| Power Factor At Reference Tempurature In Percent: |
| 0.5000 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polyethylene terephthalate |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

N/a

Shelf Life:

NSN 5910-00-241-2877

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0