## NSN 5910-00-241-9509

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-241-9509   |
|---|
| Body Style:   |
| W/o mtg facilities, terminal (s) on one end   |
| Reliability Indicator:  |
| Not established   |
| Body Diameter:  |
| 1.062 inches  |
| Body Length:  |
| 1.812 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Anode Type:   |
| Plain foil  |
| Impedance At Minimum Operating Tempurature In Ohms:   |
| 880.0   |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 10.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -40.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 350.0 dc single section   |
| Tolerance Range Per Section:  |
| -10.00/+50.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Dissipation Factor At Reference Tempurature In Percent:   |
| 12.0000   |
| Dc Leakage At Reference Temp:   |
| 88.000 microamperes   |
| Terminal Surface Treatment:   |
| Solder  |
| Case Insulation Material:   |
| Plastic   |
| Test Data Document:   |
| 81349-milc62/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 tab, solder lug

Shelf Life:

N/a

## NSN 5910-00-241-9509

Electrolytic Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0