NSN 5910-00-243-0110

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-243-0110 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.484 inches **Bushing Diameter:** 0.120 inches **Bushing Length:** 0.156 inches **Body Length:** 0.281 inches **Overall Diameter:** 0.145 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 50.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.266 inches **Quality Factor At 25 Deg Celsius:** 5000.0 **Terminal Width:** 0.030 inches **Terminal Thickness:** 0.010 inches **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type: Encased Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.300 inch-ounces and 3.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms

Mounting Facility Type And Quantity: 1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

NSN 5910-00-243-0110

Air Dielectric Variable Capacitor - Page 2 of 2



Thread Size:
0.120 inches
Capacitance Range In Picofarads:
+0.35/+3.50 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
2 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0