NSN 5910-00-243-6136

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-243-6136

Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established

Terminal Length:

0.440 inches

Body Length:

3.970 inches

Body Width:

2.970 inches

Body Height:

3.120 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.500 inches and 2.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.219 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.125 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting holes

Section Quantity:

3

Insulation Resistance At Maximum Operating Temp:

200.0 megohm-microfarads

Capacitance Value Per Section:

0.500 microfarads 3rd section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 110.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

4000.0 dc 3rd section

Tolerance Range Per Section:

-10.00 to 10.00 percent all sections

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

NSN 5910-00-243-6136

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
3 tab, solder lug and 3 connector, receptacle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0