

View Online at <https://aerobasegroup.com/nsn/5910-00-246-8723>

**Body Style:**

Rotary

**Terminal Length:**

Between 0.156 inches and 0.186 inches

**Overall Height:**

Between 0.521 inches and 0.551 inches

**Body Diameter:**

0.375 inches

**Body Height:**

0.275 inches

**Overall Diameter:**

Between 0.305 inches and 0.355 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

-1500.0 single section

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.285 inches and 0.315 inches

**Quality Factor At 25 Deg Celsius:**

500.0

**Fragility Factor:**

Moderately rugged

**Inclosure Type:**

Encapsulated

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 6.000 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10000.0 megohms

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:**

+15.0 to 60.0 single section

**Nonderated Voltage Rating And Type:**

200.0 dc continuous single section

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

+6.00 to 16.00 and -11.00/-6.00 single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.50 single section

**Material:**

Steatite base

**Precious Material And Location:**

Electrode silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0