

View Online at <https://aerobasegroup.com/nsn/5910-00-247-8598>

Body Style:

Plate-meshing

Overall Length:

Between 0.735 inches and 0.797 inches

Terminal Length:

Between 0.125 inches and 0.187 inches

Overall Height:

Between 0.441 inches and 0.465 inches

Overall Width:

Between 0.421 inches and 0.445 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

45.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-15.0/+15.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Between 0.369 inches and 0.431 inches

Fragility Factor:

Moderately rugged

Terminal Width:

0.045 inches

Terminal Thickness:

0.016 inches

Inclosure Type:

Uninclosed

Plate Quantity:

18

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise and 180.0 degrees counterclockwise

Adjustment Device Torque:

Between 2.500 inch-ounces and 10.000 inch-ounces

Plate Air Gap:

0.010 inches

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+2.2/+21.9 single section

Nonderated Voltage Rating And Type:

500.0 ac peak single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Material:

Silver capacitive electrode

Precious Material And Location:

Metal surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0