NSN 5910-00-247-8599

Body Style:

Iridium and silver

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-247-8599

| Plate-mesning |
|---|
| Overall Length: |
| 0.813 inches |
| Terminal Length: |
| 0.344 inches |
| Overall Height: |
| 1.112 inches |
| Overall Width: |
| 0.433 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| 45.0 single section |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: |
| -15.0/+15.0 single section |
| Unthreaded Mounting Hole Diameter: |
| 0.073 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.295 inches |
| Inclosure Type: |
| Uninclosed |
| Plate Quantity: |
| 20 |
| Tuning Characteristic: |
| Straight line capacity single section |
| Adjustment Device Rotation: |
| 180.0 degrees clockwise and 180.0 degrees counterclockwise |
| Adjustment Device Torque: |
| Between 2.500 inch-ounces and 10.000 inch-ounces |
| Plate Air Gap: |
| 0.010 inches |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Capacitance Range In Picofarads: |
| +2.4/+24.5 single section |
| Nonderated Voltage Rating And Type: |
| 500.0 ac peak single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Precious Material And Location: |
| All metal surfaces iridium and all metal surfaces silver |
| Precious Material: |

NSN 5910-00-247-8599

Air Dielectric Variable Capacitor - Page 2 of 2



| Terminal Type And Quantity | Terminal | Type | And | Quantity | / : |
|----------------------------|----------|-------------|-----|----------|------------|
|----------------------------|----------|-------------|-----|----------|------------|

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0