## NSN 5910-00-247-9010

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-247-9010

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
0.400 inches
Body Width:
0.100 inches
Body Height:
0.400 inches
Center To Center Distance Between Terminals Parallel To Length
0.300 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
50.0 megohm-microfarads
Capacitance Value Per Section:
22000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
25000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.3000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5910-00-247-9010

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0